

SLICKBAR™

TEMPORARY TANK BS-12



GENERAL DESCRIPTION

SLICKBAR™ TEMPORARY TANK BS-12 provides a flexible and reliable solution to the permanent or temporary containment of polluting liquids. The TEMPORARY TANK BS-12 has capacity from 4 tons (4,000 Liters) to 12 tons (12,000 Liters). The tank is durable, lightweight and compact when folded, and can be easily transported world-wide, including even remote locations. The **SLICKBAR™ TEMPORARY TANK BS-12** is ideally suited to all incidents requiring containment or wash down. The tank features an inside pocket for ease of cleaning, which can be changed separately.



SLICKBAR™ INDONESIA

The World Leader in Oil Spill Control Technology ... since 1960

PRODUCTION

SLICKBAR™ TEMPORARY TANK BS-12 has been designed as portable and light weight temporary storage unit for use in land. **SLICKBAR™** TEMPORARY TANK BS-12 is manufactured by expert teams of Oil Spill Response Equipment builders. All **SLICKBAR** products are produced and manufactured in accordance with the International Quality Assurance System ISO 9001:2008, ISO 14001:2004, and OHSAS 18001:2007.

LAYOUT OF SLICKBAR™
TEMPORARY TANK BS-12



STORAGE

The **SLICKBAR™** TEMPORARY TANK BS-12 can be stored in a marine grade aluminium box (optional). It is also equipped with wheels for increased mobility and can be moved by a forklift.

HIGH QUALITY MATERIAL

SLICKBAR™ TEMPORARY TANK BS-12 is made from PVC with a high temperature resistance. The frame and hardware are made from non-corrosive material. Complete with Polybag, so we do not need to cleaning.

TECHNICAL DATA

CAPACITY	4 tons	6 tons	8 tons	10 tons	12 tons
FRAME MATERIAL	Stainless Steel				
HARDWARE	Stainless Steel				
FABRIC MATERIAL	PVC				
COLOR OF MATERIAL	Black/Orange				
SKIRT STRENGTH	4000 N/5cm				
TEMP. RESISTANCE	-30 ~ + 70 °C				

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

SLICKBAR™ INDONESIA
The World Leaders in Oil Spill Control Technology ... since 1960

CERTIFICATES AND PATENTS

Manufacturer in Indonesia is certified with ISO 9001:2008 (Certificate No. JKT 403890), ISO 14001:2004 (Certificate No. JKT 60057267A) and OHSAS 18001:2007 (Certificate No. JKT 60057267B). SLICKBAR oil booms and accessories are protected under one or more of the following patent numbers: Indonesia 231951, ID 0 005 932, ID 0 005 933, U.S.A. 3,146,698, 3,321,92 RE 27,452 (Reissue of 3,499,290), 3,556,301, 3,564,852, 3,679, 058, 848, 417; United Kingdom 993, 227, 1,226, 040; Canada 862,401, 909, 353; France 1,403,411,69,21131;Italy 732,313,866, 809; Japan 588, 400; Belgium 735, 074; Germany S.N.P. 1929751; Holland S.N. 69, 08133; Australia 435, 835, Other U.S. and foreign patents pending.



OIL POLLUTION EQUIPMENT DIVISION

DELTA SILICON II INDUSTRIAL PARK BLOCK F2/1
Lippo Cikarang, Bekasi 17550, West Java, Indonesia
Phone : +62 21 89117311, 89117312, 89117313 Fax : +62 21 89117314
Web Site : www.slickbar.co.id ; E-mail : info@slickbar.co.id